



CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)
Issue date: 2025-09-09 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Trade name : CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g
Product code : 1006347
Part number : 75110

1.2. Recommended use and restrictions on use

Recommended use : Mass air flow sensor cleaner
Restrictions on use : None known

1.3. Supplier

Manufactured or sold by:

CRC Canada Co.
83 Galaxy Blvd.
Unit 35 - 37
Toronto, ON M9W 5X6
Canada
T 416-847-7750
crcindustries.ca

1.4. Emergency telephone number

Emergency number : 800-424-9300 (CHEMTREC)
24-Hour Emergency

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Aerosol, Category 1	Extremely flammable aerosol. Pressurized container; may burst if heated.
Physical hazards not otherwise classified, Category 1	
Acute toxicity (oral), Category 4	Harmful if swallowed.
Skin corrosion/irritation, Category 2	Causes skin irritation.
Serious eye damage/eye irritation, Category 2B	Causes eye irritation.
Reproductive toxicity, Category 1A	May damage fertility or the unborn child.
Specific target organ toxicity, Single exposure, Category 1	Causes damage to organs (central nervous system, eyes).
Specific target organ toxicity – Single exposure, Category 3, Narcosis	May cause drowsiness or dizziness.
Specific target organ toxicity, Repeated exposure, Category 1	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	May be fatal if swallowed and enters airways.
Hazardous to the aquatic environment, Acute Hazard, Category 2	Toxic to aquatic life.
Hazardous to the aquatic environment, Chronic Hazard, Category 2	Toxic to aquatic life with long lasting effects.

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

: Danger

Hazard statements (GHS CA)

: Extremely flammable aerosol
Pressurized container; may burst if heated
Harmful if swallowed
May be fatal if swallowed and enters airways
Causes skin and eye irritation
May cause drowsiness or dizziness
May damage fertility or the unborn child
Causes damage to organs (central nervous system, eyes).
Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS CA)

: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Do not eat, drink or smoke when using this product.
Do not breathe vapors, spray, mist.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, protective clothing, eye and face protection.
Wash hands thoroughly after handling.
IF SWALLOWED: Immediately call a POISON CENTER or a doctor.
Rinse mouth.
Do NOT induce vomiting.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or a doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice or attention.
IF ON SKIN: Wash with plenty of water.
If skin irritation occurs: Get medical advice or attention.
Take off contaminated clothing and wash it before reuse.
IF exposed or concerned: Call a POISON CENTER or a doctor.
Store in a well-ventilated place.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container in accordance with local/regional/national regulations.

2.3. Other hazards

Other hazards which do not result in classification

: Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

2.4. Unknown acute toxicity (GHS CA)

No additional information available

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Naphtha (petroleum), hydrotreated light	Naphtha (petroleum), hydrotreated light	CAS-No.: 64742-49-0	45 – 70
Carbon dioxide	Carbon dioxide	CAS-No.: 124-38-9	3 – 7
Methanol	Methanol ; Methyl alcohol	CAS-No.: 67-56-1	1 – 5
Hexane	n-Hexane ; Hexane	CAS-No.: 110-54-3	1 – 5
2,2,4-trimethylpentane	2,2,4-Trimethylpentane	CAS-No.: 540-84-1	0.5 – 1.5

Comments : The exact percentage (concentration) of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Even small amounts (30-250 ml methanol) may be fatal. Symptoms are stomach ache, nausea, vomiting, dullness, visual disorder and blindness. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Do not use mouth-to-mouth method if victim ingested the substance. Call a physician immediately.

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes eye irritation. Exposed may experience eye tearing, redness and discomfort.

Symptoms/effects after ingestion : Harmful if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Chronic symptoms : May damage fertility or the unborn child.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water fog. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurized container may rupture when exposed to heat or flame.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Remove ignition sources. Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
Personal Precautions, Protective Equipment and Emergency Procedures : Wear appropriate protective equipment and clothing during clean-up.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.
Methods for cleaning up : Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination. Notify authorities if product enters sewers or public waters.
Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Exposure to high temperature may cause can to burst. Prevent the build-up of electrostatic charge. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not use if spray button is missing or defective. Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Do not breathe mist, spray, vapors. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. For product usage instructions, see the product label.
- Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Level 3 Aerosol. Store locked up. Store in a well-ventilated place. Keep in fireproof place. Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- Storage area : Store away from heat.
- Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Carbon dioxide (124-38-9)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	9000 mg/m ³
	5000 ppm
OEL STEL	54000 mg/m ³
	30000 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Carbon dioxide
VECD (OEL STEV)	54000 mg/m ³
	30000 ppm
VEMP (OEL TWA EV)	9000 mg/m ³
	5000 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Carbon dioxide (124-38-9)	
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	15000 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	9000 mg/m ³ 5000 ppm
OEL STEL	54000 mg/m ³ 30000 ppm
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	9000 mg/m ³ 5000 ppm
OEL STEL	54000 mg/m ³ 30000 ppm
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	9000 mg/m ³ 5000 ppm
OEL STEL	54000 mg/m ³ 30000 ppm
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Carbon dioxide (124-38-9)	
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWAEV	5000 ppm 30000 ppm
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	9000 mg/m ³ 5000 ppm
OEL STEL	54000 mg/m ³ 30000 ppm
Notations and remarks	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Carbon dioxide
OEL TWA	5000 ppm
OEL STEL	30000 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Methanol (67-56-1)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Methanol (Methyl alcohol)
OEL TWA	262 mg/m ³ 200 ppm
OEL STEL	328 mg/m ³ 250 ppm
Notations and remarks	Substance may be readily absorbed through intact skin.
Regulatory reference	Alberta Regulation 191/2021

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Methanol (67-56-1)	
Canada (Quebec) - Occupational Exposure Limits	
Local name	Methyl alcohol (Methanol)
VECD (OEL STEV)	328 mg/m ³
	250 ppm
VEMP (OEL TWAEV)	262 mg/m ³
	200 ppm
Notations and remarks	Pc
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Skin (the substance that contribute significantly to the overall exposure by the skin route)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	262 mg/m ³
	200 ppm
OEL STEL	328 mg/m ³
	250 ppm
Notations and remarks	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Headache; eye dam; dizziness; nausea
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	262 mg/m ³
	200 ppm
OEL STEL	328 mg/m ³
	250 ppm

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Methanol (67-56-1)	
Notations and remarks	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	262 mg/m ³ 200 ppm
OEL STEL	328 mg/m ³ 250 ppm
Notations and remarks	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Methyl alcohol (methanol)
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Methyl alcohol (methanol)
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Skin
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Methanol
OEL TWAEV	200 ppm 250 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	262 mg/m ³ 200 ppm

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Methanol (67-56-1)	
OEL STEL	328 mg/m ³ 250 ppm
Notations and remarks	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Methyl alcohol (methanol)
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	Skin
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Naphtha (petroleum), hydrotreated light (64742-49-0)	
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Hexane (Commercial, <54% n-hexane)
OEL TWA	100 ppm

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Naphtha (petroleum), hydrotreated light (64742-49-0)	
Notations and remarks	TLV® Basis: Peripheral neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Hexane (110-54-3)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m ³ 50 ppm
Notations and remarks	Substance may be readily absorbed through intact skin.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	n-Hexane
VEMP (OEL TWAEV)	176 mg/m ³ 50 ppm
Notations and remarks	Pc
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	20 ppm
Notations and remarks	Skin (the substance that contribute significantly to the overall exposure by the skin route)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m ³ 50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m ³ 50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hexane (110-54-3)	
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m ³ 50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Hexane (n-Hexane)
OEL TWA	50 ppm
OEL STEL	62.5 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Hexane (n-Hexane)
OEL TWA	50 ppm
OEL STEL	62.5 ppm
Notations and remarks	Skin
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWAEV	50 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m ³ 50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Hexane (n-Hexane)

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hexane (110-54-3)	
OEL TWA	50 ppm
OEL STEL	62.5 ppm
Notations and remarks	Skin
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear fire/flammable resistant/retardant clothing.

Hand protection:

Wear protective gloves such as: Nitrile. Polyvinylchloride (PVC). Viton/butyl

Eye protection:

Wear safety glasses with side shields (or goggles).

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Additional Regulatory Information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless
Odor	: Alcoholic
Melting point	: -97.8 °C (-144 °F) estimated
Freezing point	: -97.8 °C (-144 °F) estimated
Boiling point	: -78.5 °C (-109.3 °F) estimated
Flammability (solid, gas)	: Not applicable
Explosion limits	: No data available
Flash point	: < -17.8 °C (< 0 °F) estimated
Auto-ignition temperature	: 254 °C (489.2 °F) estimated
Decomposition temperature	: No data available
pH	: No data available
Viscosity, kinematic	: No data available

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Vapor pressure	: No data available
Evaporation rate	: Very fast
Density	: No data available
Relative density	: 0.7
Relative vapor density at 20°C	: No data available
Particle characteristics	: No data available

9.2. Additional Regulatory Information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Extremely flammable aerosol. Pressurized container: may burst if heated.
Possibility of hazardous reactions	: May mass explode in fire. Heating may cause a fire or explosion.
Conditions to avoid	: High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: Formaldehyde. Carbon oxides (CO, CO ₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g	
ATE CA (oral)	526.578 mg/kg body weight
Methanol (67-56-1)	
LD50 oral rat	100 mg/kg Source: National Institute of Environmental Research NCIS
LD50 dermal rabbit	300 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	85000 mg/l
Naphtha (petroleum), hydrotreated light (64742-49-0)	
LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 3160 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 23.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat [ppm]	73680 ppm Source: IUCLID
LC50 Inhalation - Rat (Dust/Mist)	> 23300 mg/l
Hexane (110-54-3)	
LD50 oral rat	24 ml/kg Source: ECHA
LD50 dermal rabbit	> 3350 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	> 17600 mg/l
LC50 Inhalation - Rat (Vapors)	259.354 mg/l Source: ECHA

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

2,2,4-trimethylpentane (540-84-1)	
LD50 oral rat	> 2500 mg/kg Source: IUCLID, echemportal; HSNO CCID,TOMES;LOLI;
LD50 dermal rat	> 690 mg/kg Source: IUCLID;
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 33.52 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
LC50 Inhalation - Rat (Vapors)	> 34.7 mg/l Source: IUCLID,TOMES;LOLI;
Skin corrosion/irritation	: Causes skin irritation.
Carbon dioxide (124-38-9)	
pH	3.2 Source: HSDB
Methanol (67-56-1)	
pH	12.1 Source: Gestis
Serious eye damage/irritation	: Causes eye irritation.
Carbon dioxide (124-38-9)	
pH	3.2 Source: HSDB
Methanol (67-56-1)	
pH	12.1 Source: Gestis
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: May damage fertility or the unborn child.
STOT-single exposure	: Causes damage to organs (central nervous system, eyes). May cause drowsiness or dizziness.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Methanol (67-56-1)	
NOAEC (inhalation, rat, 28 days)	6.66 mg/l
NOAEC (inhalation, rat, 90 days)	1.06 mg/l
Naphtha (petroleum), hydrotreated light (64742-49-0)	
LOAEC (inhalation, rat, vapor, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapor, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male
Hexane (110-54-3)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
2,2,4-trimethylpentane (540-84-1)	
NOAEC (inhalation, rat, vapor, 90 days)	24.3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Methanol (67-56-1)	
Viscosity, kinematic	0.692 mm ² /s

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Naphtha (petroleum), hydrotreated light (64742-49-0)	
Viscosity, kinematic	0.67 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation. Exposed may experience eye tearing, redness and discomfort.
Symptoms/effects after ingestion	: Harmful if swallowed. Aspiration may cause pulmonary edema and pneumonitis.
Chronic symptoms	: May damage fertility or the unborn child.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Carbon dioxide (124-38-9)	
LC50 - Fish [1]	35 mg/l Source: HSDB

Methanol (67-56-1)	
LC50 - Fish [1]	15400 mg/l Source: ECHA
EC50 - Crustacea [1]	> 1000 mg/l
EC50 - Other aquatic organisms [1]	10000 mg/l waterflea
EC50 - Other aquatic organisms [2]	12000 mg/l
ErC50 algae	20300 mg/l
EC50 96h - Algae [1]	22000 mg/l Source: ECHA
NOEC chronic fish	446.7 mg/l Test organisms (species): Pimephales promelas Duration: '28 d'
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Naphtha (petroleum), hydrotreated light (64742-49-0)	
LC50 - Fish [1]	> 3 mg/l
LC50 - Other aquatic organisms [1]	2.6 mg/l Source: IUCLID
EC50 - Other aquatic organisms [1]	4.6 mg/l waterflea
EC50 - Other aquatic organisms [2]	10 mg/l
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Hexane (110-54-3)	
LC50 - Fish [1]	> 1 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	50 mg/l waterflea

2,2,4-trimethylpentane (540-84-1)	
LC50 - Fish [1]	1.287 mg/l Source: ECOSAR
EC50 - Crustacea [1]	0.988 mg/l Source: ECOSAR
EC50 96h - Algae [1]	1.16 mg/l Source: ECOSAR

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

2,2,4-trimethylpentane (540-84-1)	
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Persistence and degradability	No data is available on the degradability of this product.
-------------------------------	--

12.3. Bioaccumulative potential

Carbon dioxide (124-38-9)

Partition coefficient n-octanol/water (Log Pow)	0.83 Source: ISCS
---	-------------------

Methanol (67-56-1)

BCF - Fish [1]	< 10 l/kg
Partition coefficient n-octanol/water (Log Pow)	-0.77 Source: HSDB, CHemIDplus

Naphtha (petroleum), hydrotreated light (64742-49-0)

Partition coefficient n-octanol/water (Log Pow)	2.1 – 6 Source: IUCLID
---	------------------------

Hexane (110-54-3)

Partition coefficient n-octanol/water (Log Pow)	3.9 Source: ICSC
---	------------------

2,2,4-trimethylpentane (540-84-1)

Partition coefficient n-octanol/water (Log Pow)	4.5 Source: IUCLID
---	--------------------

12.4. Mobility in soil

Methanol (67-56-1)

Mobility in soil	2.75 Source: HSDB
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	-0.8860566 – -0.21467016

2,2,4-trimethylpentane (540-84-1)

Mobility in soil	3543
------------------	------

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations. Dispose of contents/container in accordance with local/regional/national regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not allow to enter sewers, surface or groundwater.
Product/Packaging disposal recommendations	: Contents under pressure. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g



Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with TDG / IMDG / IATA

TDG	IMDG	IATA
14.1. UN number		
UN1950	1950	1950
14.2. Proper Shipping Name		
AEROSOLS (Limited quantity)	AEROSOLS (Limited quantity)	Aerosols, flammable (Limited quantity)
14.3. Transport hazard class(es)		
LTD QTY	LTD QTY	LTD QTY
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Marine Pollutant Exception		

14.6. Special precautions for user

TDG

- TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gases
UN-No. (TDG) : UN1950
TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.
- Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L

IMDG

- Class (IMDG) : 2 - Gases
Special provision (IMDG) : 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP200
Packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

IATA

Class (IATA) : 2 - Gases
PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg
Special provision (IATA) : A145, A167, A802
ERG code (IATA) : 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

All components of this product are listed on the DSL, NDSL, or are exempt from the inventory requirements.

Name	CAS-No.	Regulatory reference
Carbon dioxide	124-38-9	Listed on the Canadian DSL (Domestic Substances List)
Methanol	67-56-1	Listed on the Canadian DSL (Domestic Substances List)
Naphtha (petroleum), hydrotreated light	64742-49-0	Listed on the Canadian DSL (Domestic Substances List)
Hexane	110-54-3	Listed on the Canadian DSL (Domestic Substances List)
2,2,4-trimethylpentane	540-84-1	Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Carbon dioxide (124-38-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

CRC® SensorKleen™ Mass Air Flow Sensor Cleaner, 311 g

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Methanol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Naphtha (petroleum), hydrotreated light (64742-49-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Hexane (110-54-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

2,2,4-trimethylpentane (540-84-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.2. Other Regulatory Information

Volatile Organic Compound Concentration Limits for Certain Products Regulations: SOR/2021-268

VOC content	95 %
Product Category	Single Purpose Cleaner, Not regulated.

SECTION 16: Other information

Issue date : 09-09-2025

Other information : 1750769.
Author : Joshua Weir

Safety Data Sheet (SDS), Canada, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co.